

# Single Longitudinal Mode Laser

## Specifications

<b>Model Number</b>	<b>SLM-IR1342-5000-DB</b>
<b>Optical Specifications</b>	
Wavelength	1342 nm
Center Wavelength Deviation	+/- 1 nm
Output Power	1000 ~ 5000 mW
M <sup>2</sup>	< 1.3
Longitudinal Mode	Single
Transverse Mode	TEM00
Power Stability (over 4 hours) (rms)	< 5 % (optional: < 1%, < 3%)
Operating Mode	CW
Polarization Ratio	> 100:1
Beam Diameter at the Aperture (1/e <sup>2</sup> )	~ 1.5mm
Spectral Linewidth	< 0.00001 nm
Noise of Amplitude (rms, 1Hz-20MHz)	< 0.5 %
Beam Divergence (Full Angle)	< 1.6 mrad
Warm-up time	< 12 minutes
Pointing Stability after Warm-up	< 0.05
Beam Height from Base Plate	58 mm
Working Temperature	20 to 30 ° C
Cooling Mode	Water Cooled
Estimated Lifetime (MTTF)	10000 hours
Warranty Time	1 year
<b>Mechanical Specifications</b>	
Dimension of Laser Head	427 (L) x 190 (W) x 83 (H) mm
Dimension of Power Supply	307 (L) x 168 (W) x 123 (H) mm
Water Chiller	280 (L) x 230 (W) x 380 (H) mm
Dimensional Tolerances	+/- 1 mm